



econfloor

P O L S K A S P. Z O O.

PRODUCT DATA SHEET

ENGLISH

COLLECTION LA BOHEME 55

TECHNICAL DATA

LA BOHEME 55

Product	SPC Rigid Vinyl floor, La Boheme 55	
Thickness	5.7 mm	
Wear layer	0.55 mm	
Clicking system	Pushdown Click-system	
IXPE-Aluminium underlay	1.7 mm (incl. 0.2 mm aluminium foil)	
Features	Waterproof, Wear-resistant, Anti-slip, Rot-, Fire-, Sound-, Mold-proof	
Measurements	1280 x 230 mm	
Surface treatment	Ceramic & UV coated, EIR (Embossed in register), Hand-brushed wood	
Advantages	Easy click-system to install, Labor costs saving, Strong stability, Eco-friendly	
Density	2.0g/cm ³	
Technical data	Test method	Result
Abrasion resistance	EN 660-2	42
Slip resistance	EN 13893/DIN 51130	R11 Class
Color fastness	EN ISO 105-B02	≥6
Castor chair resistance	ISO TR4918	Passed
Chemical resistance	EN ISO 26987	Excellent
Flame retardency	EN 13501-01	Bfl-s1
Toxicity	EN 71	Non toxic
Dimensional stability	EN434	< 0.06%
Castor chair effect	EN425	Good
Underfloor heating	EN12524	Suitable
Antibacterial properties	EN846	Very good
Peel strength	EN	100N/5cm
Load test	EN433	0.03
Heat resistance	---	0.026 m ² /KW