

Technical Data Sheet



econfloor
POLSKA SP. Z O.O.

3-layer parquet, wide plank (“castle plank”), Kernig range

European oak, hand-scraped, brown natural oiled, drop-down click system

Article Nr. **50231Y**

Measurements

| | |
|-----------|---------|
| Length | 2200 mm |
| Width | 260 mm |
| Thickness | 15 mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | Approx. 4 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG, Terralin industrial oil 2A019, dark brown

Regular maintenance recommended

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin Click on the long side, Drop Down Click on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 6 planks | 3,432 m ² |
| 1 pallet = 40 packages = 260 planks | 137,280 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fi}-s1

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet

3-layer parquet, plank flooring, Country range

European oak, brushed, natural oiled, drop-down click system

Article Nr. 50107YE

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 15mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | Approx. 4 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG, Terralin industrial oil 2A019, colorless

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin Click on the long side, Drop Down Click on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

| | |
|-----------------------------|---------------------|
| Formaldehyde emission class | E 1 |
| Eire protection class | D _{fi} -s1 |
| Thermal resistance | 0,13 W/mk |

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet

3-layer parquet, plank flooring, Country range

European oak, white natural oiled, drop-down click system

Article Nr. 50108NE

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 15mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | Approx. 4 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

WOCA white natural oil, oxidatively cured – pre-oiled (regular maintenance recommended)

Woodcare A/S, WOCA Industrial Oil 1582

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Välinge 2G Click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fi}-s1

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet



3-layer parquet, plank flooring, Markant range

European oak, smoked, heavily brushed, natural oiled & hardwax oil, drop-down click system

Article Nr. 50187YE

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 14 mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 3 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove (0.75 mm)

Surface

Bergolin GmbH & Co. KG clear Terralux – finished oiled

Terralin industrial oil 2A019, colorless

LOBA waxing oil – Next model, finished oiled

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fi}-s1

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet

3-layer parquet, plank flooring, Markant range,

European oak, hand-scraped, natural oiled, drop-down click system

Article Nr. **50204YE**

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 15 mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 3 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

BBERgolin GmbH & Co. KG, Terralin industrial oil 2A019, colorless

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fi}-s1

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet

3-layer parquet, plank flooring, Markant range

European oak, brushed, white natural oiled, drop-down click system

Article Nr. 50193Y

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 14 mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 3 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG, Terralin industrial oil 2A019 (2A019-0001), white natural oil

Regular maintenance recommended

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fi}-s1

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet

3-layer parquet, plank flooring, Markant range,

European oak, brushed, natural oiled, drop-down click system

Article Nr. 50191Y

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 14 mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 3 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG, Terralin industrial oil 2A019, colorless (regular maintenance recommended)

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fi}-s1

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet

3-layer parquet, plank flooring, Classic range

European oak, brushed, UV-oiled, drop-down click system

Article Nr. 50105YE

Measurements

| | |
|-----------|---------|
| Length | 1900 mm |
| Width | 190 mm |
| Thickness | 15 mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 4 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG clear Terralux UV oil – pre-finished
Terralux UV oil roller coating 2L154-1, colorless

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 8 planks | 2,888 m ² |
| 1 pallet = 40 packages = 320 planks | 115,520 m ² |

Properties

| | |
|-----------------------------|---------------------|
| Formaldehyde emission class | E 1 |
| Eire protection class | D _{fi} -s1 |
| Thermal resistance | 0,13 W/mk |

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet



econfloor
POLSKA SP. Z O.O.

3-layer parquet, wide plank, Kernig range

European oak, brushed, natural oiled, drop-down click system

Article Nr. 50227Y

Measurements

| | |
|-----------|---------|
| Length | 2200 mm |
| Width | 260 mm |
| Thickness | 15mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 4 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG, Terralin industrial oil 2A019, colorless
-regular maintenance recommended

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 6 planks | 3,432 m ² |
| 1 pallet = 40 packages = 260 planks | 137,280 m ² |

Properties

| | |
|-----------------------------|---------------------|
| Formaldehyde emission class | E 1 |
| Eire protection class | D _{fl} -s1 |
| Thermal resistance | 0,13 W/mk |

Suitable for hot-water underfloor heating in accordance with applicable standards
Suitable for proper floating installation or full-surface bonding
Please observe our installation instructions for laying

As of August 2023; subject to change

Technical Data Sheet



econfloor
POLSKA SP. Z O.O.

3-layer parquet, wide plank, Kernig range

European oak, brushed, white natural oiled, drop-down click system

Article Nr. 50228Y

Measurements

| | |
|-----------|---------|
| Length | 2200 mm |
| Width | 260 mm |
| Thickness | 15mm |

Structure

| | |
|---------------|---------------------------|
| Wear layer | approx. 4 mm oak |
| middle layer | 9 mm poplar wood lamellas |
| backing layer | 2 mm poplar veneer |

4-sided V-groove

Surface

Bergolin GmbH & Co. KG, Terralin industrial oil 2A019, 2A019-0001
-regular maintenance recommended

Glue

DYNEA ASA, Prefere 4405 or equivalent

Joint / locking system

Unilin click system on the long side

Drop-down click system on the short side

Country of manufacture

China

Packaging

| | |
|-------------------------------------|------------------------|
| 1 package = 6 planks | 3,432 m ² |
| 1 pallet = 40 packages = 260 planks | 137,280 m ² |

Properties

Formaldehyde emission class E 1

Eire protection class D_{fl-s1}

Thermal resistance 0,13 W/mk

Suitable for hot-water underfloor heating in accordance with applicable standards

Suitable for proper floating installation or full-surface bonding

Please observe our installation instructions for laying

As of August 2023; subject to change