



econfloor

P O L S K A S P. Z O O.

PRODUCT DATA SHEET

-EN-

COLLECTION LA VILLI BIG SIZE 65

TECHNICAL DATA

LA VILLI BIG SIZE 65

Product	SPC Rigid Vinyl floor	
Thickness	6.7 mm	
Wear layer	0.55 mm	
Clicking system	Pushdown Click-system	
IXPE-Aluminium underlay	1.7 mm (incl. 0.2 mm aluminium foil)	
Features	Waterproof, Wear-resistant, Anti-slip, Rot-, Fire-, Sound-, Mold-proof	
Measurements	940 x 470 mm	
Surface treatment	Ceramic & UV coated, EIR (Embossed in register), Hand-brushed wood	
Advantages	Easy click-system to install, Labor costs saving, Strong stability, Eco-friendly	
Density	2.0g/cm ³	
Technical data	Test method	Result
Abrasion resistance	EN 660-2	42
Slip resistance	EN 13893/DIN 51130	R11 Class
Color fastness	EN ISO 105-B02	≥6
Castor chair resistance	ISO TR4918	Passed
Chemical resistance	EN ISO 26987	Excellent
Flame retardency	EN 13501-01	Bfl-s1
Toxicity	EN 71	Non toxic
Dimensional stability	EN434	< 0.06%
Castor chair effect	EN425	Good
Underfloor heating	EN12524	Suitable
Antibacterial properties	EN846	Very good
Peel strength	EN	100N/5cm
Load test	EN433	0.03
Heat resistance	---	0.026 m ² /KW
VOC	EN 16516	A+